

### **Overview**

Count on productivity, premium quality, maximum uptime, and the strongest security[1]

HP LaserJet printers power office productivity with a smart, streamlined design that's reliable and hassle-free. Count on premium quality, maximum uptime, and the strongest security[1]—all intended to drive successful organizations forward.

#### **Professional color printing**

Print premium, professional-quality documents with vivid color images and graphics.

# Minimal interruptions. Maximum productivity.

Change the toner and drum in seconds. Both are easily accessible and come already installed out of the box.

#### The world's most secure printing[1]

Each printer in your fleet checks its operating code and repairs itself from attacks.

## **Features**

Premium color using Enhanced print mode	Original HP toner and drums with JetIntelligence—and HP ColorSphere 3
Wide range of paper-handling accessories	Fast first-page printing with first page out as fast as 5.7 seconds
Fast, easy supplies replacement	Minimal maintenance with long-life supplies

[1] Based on HP review of 2018 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://hp.com/go/PrintersThatProtect. For more information: http://hp.com/go/printersecurityclaims

# **Specifications**

Drint Decelution Technologies	UD ImageDEt 4000 Fine Lines (1200v1200 dpi) Ovislation (200v200 dpi)
Print Resolution Technologies	HP ImageREt 4800, Fine Lines (1200x1200 dpi), Quickview (300x300 dpi)
Print speed black (ISO, A4)	Up to 46 ppm
Print speed black (ISO, letter)	Up to 45 ppm
Print Speed Color (ISO)	Up to 46 ppm
Print speed color (ISO)	Up to 45 ppm
Print speed	Print speed up to 45 ppm (black) and 45 ppm (color)
Functions	Print
Duplex printing	Automatic (standard)
Duty cycle (monthly, A4)	Up to 150,000 pages
Duty cycle (monthly, letter)	Up to 150,000 pages <sup>[10]</sup>
Printer smart software features	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB
Energy savings feature technology	Instant-on Technology
Replacement cartridges	W9020MC HP Black Managed LaserJet Toner Cartridge (~38,000 pages); W9021MC HP Cyan Managed LaserJet Toner Cartridge (~35,000 pages); W9022MC HP Magenta Managed LaserJet Toner Cartridge (~35,000 pages); W9023MC HP Yellow Managed LaserJet Toner Cartridge (~35,000 pages); W9018MC HP Managed LaserJet Imaging Drum (~75,000 pages, universal for all 4 colors) <sup>[7]</sup>
Supplies feature	HP JetIntelligence Cartridge
Connectivity, standard	1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 rear host ports; 1 walkup USB 2.0 host port; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network port; 1 Hardware Integration Pocket 2nd generation (HIP2)
Connectivity, optional	HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A, (Dual band Wireless Station and Wi-Fi Direct functionality); HP Jetdirect 2900nw Print Server J8031A (Dual band Wireless Station)
Network capabilities	Yes, via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional)
Wireless capability	Optional, enabled with purchase of a wireless hardware accessory: HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A, (Dual band Wireless Station and Wi-Fi Direct functionality) HP Jetdirect 2900nw Print Server J8031A (Dual band Wireless Station)
Mobile printing capability	Apple AirPrint™; Google Cloud Print™; HP ePrint; HP Roam; Mopria™ Certified
Network protocols, supported	IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print

Software included	No software solutions are included in the Box, only on http://hp.com, http://123.hp.com
Compatible Operating Systems	Windows 11; Windows 10; Windows 8; Windows 8.1; Windows 7; Windows Client OS; Android; iOS; Mobile OS; macOS 10.12 Sierra; macOS 10.13 High Sierra; macOS 10.14 Mojave <sup>[12]</sup>
Sustainable impact specifications	Mercury free
Energy star certified	Yes
Ecolabels	EPEAT® Silver; CECP; ENERGY STAR® qualified <sup>[13]</sup>
Blue Angel compliant	Yes, Blue Angel DE-UZ 219—only ensured when using Original HP supplies
Display area (imperial)	2.7 in
Display area (metric)	6.86 cm
Display	2.7 in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad
Minimum dimensions (W $\times$ D $\times$ H)	556 x 589 x 399 mm (Without paper trays extended)
Minimum dimensions (W x D x H)	21.9 x 23.2 x 15.7 in (Without paper trays extended)
Weight	45.1 kg <sup>[3]</sup> (With print cartridges)
Weight	99.4 lb (With print cartridges)
Power consumption	850 watts (max. printing), 820 watts (typical printing) 46 watts (Ready), 0.6 watts (Sleep), 0.6 watts (HP Auto-Off/Auto On), 0.08 watts (Auto-Off), 0.08 watts (Off) <sup>[4]</sup>
Power supply type	Built-in 115V or 220V Power Supply
What's in the box	HP Color LaserJet Managed E75245dn printer; Four preinstalled HP LaserJet toner cartridges; Guide (Getting started Guide); Power cord[1, 7] [1,6]
Manufacturer Warranty	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (wty code 4G; wty ID A001)

# Additional specifications

Accessories	HP LaserJet 550-sheet Paper Tray T3V27A, HP LaserJet Stand T3V28A, HP LaserJet 2x550-sheet Paper Tray and Stand T3V29A, HP LaserJet 2700-sheet HCI Paper Tray and Stand T3V30A, HP High-Performance Secure Hard Disk (FIPS Drive) B5L29A, HP Internal USB Ports B5L28A, HP Foreign Interface Harness B5L31A, HP 1 GB DDR3x32 144-Pin 800MHz S0DIMM E5K48A Accy, HP 2 GB DDR3x32 144-Pin 800MHz S0DIMM Accy E5K49A, HP SmartCard NIPRNet Solution for US Government CC543B, HP SmartCard SIPRNet Solution for US Government F8B30A, HP Jetdirect 2900nw Print Server J8031A, HP Jetdirect 3100w BLE/NFC/Wireless Accy 3JN69A, HP USB Universal Card Reader X3D03A, HP HIP2 Keystroke Reader Y7C05A, HP Legic Reader 4QL32A, HP TAA Version secure hard disk drive 5EL03A, HP 2GB 144-Pin DDR3 TAA Version DIMM 2NR09A
Acoustic power emissions (active, printing)	6.7 B(A)
Acoustic power emissions (ready)	4.5 B(A)
Acoustic pressure emissions bystander (active, printing)	51 dB(A)
Acoustic pressure emissions bystander (ready)	29 dB(A)
Additional information about HP	http://www.hp.com
Additional information about HP in the countries	hp.com
Automatic paper sensor	Yes
Bottom margin (A4)	5 mm
Business filter	cMPS
Cable included	No, please purchase USB cable separately
Capacity	16 GB eMMC by default
Cartons per layer	1
Compatible Network Operating Systems	Windows 11; Windows Server; Linux; Citrix; UNIX; Novell
Component type	Printer
Control panel	2.7 in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad
Count of layers in pallet	4
Country of origin	Made in Japan
Datasheet photo 1	Publication photos/T3U64A.jpg
Datasheet photo 4	Publication photos/E75245dn walkaround.jpg

Downloadable software	From http://123.hp.com, HP Easy Start (Guided Software Install for Windows and Mac); From http://hp.com for Windows OS, Full-solution software and drivers, Basic-solution software and drivers, HP PCL6 XPS Discrete Print Driver, Product Documentation and Support; From http://hp.com for Mac OS, HP Easy Start (Guided Software Install), HP Mac PS Print Driver, HP Easy Admin; For Mobile OS, iOS For more information see http://hp.com/go/businessmobileprinting; Android For more information see http://hp.com/go/businessmobileprinting; From http://hp.com for printer administrators, Printer Administrator Resource Kit (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator), HP Universal Print Drivers PCL6 GDI & PS GDI for Windows, HP ePrint Software (Mobile Driver for Windows); SAP Print Drivers for more information see http://support.hp.com/us-en/document/c05051702; HP Web JetAdmin, HP JetAdvantage Security Manager, HP Roam, HPLIP Linux Printer Driver for more information see http://hplipopensource.com/hplip-web/index.html; Unix Model Script Printer Driver for more information see http://hp.com/go/unixmodelscripts, ReadIris
Driver updates	Current HP printer drivers and software can be obtained from the HP Customer Care Web site: In the US, go to http://www.hp.com/support/colorljE75245; Outside the US, go to http://www.hp.com/support 1 Select the country/region 2 Select Software and Drivers 3 Select Printer 4 Enter a product name/number 5 The operating system is automatically detected 6 Select a driver or other software 7 Then select DOWNLOAD
Duty cycle note	Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
Dynamic security	Dynamic security enabled printer
Electromagnetic compatibility	CISPR 22:2008 (International) - Class A, CISPR32:2012 (International) - Class A, EN 55032: 2012 (EU) - Class A, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010, EMC Directive 2014/30/EU, FCC CFR 47 Part 15 Class A/ICES-003, Issue 6 Class A. Other EMC approvals as required by individual countries.
Engine life	600000
Envelope Feeder	No
FCC Class A emissions	FCC Class A emissions - for use in commercial environments, not residential environments
Finished output handling	Sheetfed
First page out black (A4, ready)	As fast as 5.7 sec
First page out black (A4, sleep)	As fast as 11.5 sec
First page out black (letter, ready)	As fast as 5.7 sec
First page out black (letter, sleep)	As fast as 11.5 sec
First page out color (A4, ready)	As fast as 6.1 sec
First page out color (A4, sleep)	As fast as 11.5 sec
First page out color (letter, ready)	As fast as 6.1 sec
First page out color (letter, sleep)	As fast as 11.5 sec

Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts
Input capacity	Up to 650 sheets (80 g/m² paper)
Internal Storage	Optional 500 GB HDD: HP Secure High Performance Hard Disk drive 500 GB B5L29A; HP FIPS-140-2 Secure Hard Disk Drive 5EL03A
Left margin (A4)	5 mm
Mac compatible	Yes
Maximum Memory	3.5 GB <sup>[9]</sup>
Maximum dimensions (W x D x H)	1051 x 992 x 443 mm
Maximum dimensions (W x D x H)	41.4 x 39.1 x 17.4 in
Maximum input capacity (sheets)	Up to 4450 (80 g/m² paper)
Maximum output capacity (sheets)	Up to 250 sheets
Maximum print area	310 x 447 mm
Media size, tray 1	A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL
Media size, tray 2	A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS)
Media size, tray 3	A3, A4, A4-R, A5, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS)
Media sizes supported	100-sheet multipurpose Tray 1: A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL; 550-sheet input Tray 2: A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 1x550 and 2x550 tray and stand: A3, A4, A4-R, A5, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 2700-sheet HCI paper tray and stand: A4
Media sizes supported	100-sheet multipurpose Tray 1: Statement, $3 \times 5$ index card, $4 \times 6$ index card, $5 \times 7$ index card, $5 \times 8$ index card, Letter, Letter-R, Legal, Executive, $11 \times 17$ in; $8.5 \times 13$ , $12 \times 18$ , Envelopes: #9, #10, Monarch; $550$ -sheet input Tray 2: Letter, Letter-R, Legal, Executive, $8.5 \times 13$ , $11 \times 17$ in; Optional $1 \times 550$ and $2 \times 550$ tray and stand: Letter, Letter-R, Legal, Executive, $8.5 \times 13$ , $11 \times 17$ in, $12 \times 18$ ; Optional $2 \times 700$ -sheet HCI paper tray and stand: Letter
Media sizes supported, key	10 x 15 cm; A4; A3; Envelopes
Media sizes supported, key	4 x 6 in; Letter; Legal; 11 x 17 in; Envelopes

Media sizes, custom	100 -sheet multipurpose Tray 1: 2.5 x 5 to 12.6 x 18 in; 550-sheet input Tray 2: 5.8 x 5.8 to 11.7 x 17 in; Optional 1x550 and 2x550 tray and stand: $5.8 \times 5.8$ to 12.6 x 18 in; Optional 2700-sheet HCI paper tray and stand: 11 x 8.27 to 11.7 x 8.5 in
Media sizes, custom	100-sheet multipurpose Tray 1: 64 x 127 to 320 x 457.2 mm; 550-sheet input Tray 2: 148 x 148 to 297 x 431.8 mm; Optional 1x550 and 2x550 tray and stand: 148 x 148 to 320 x 457.2 mm; Optional 2700-sheet HCI paper tray and stand: 279.4 x 210 mm to 297 x 215.9
Media type and capacity, tray 1	Sheets: 100 (80 g/m²) Transparencies: 50 Envelopes: 10 Labels: 50
Media type and capacity, tray 2	Sheets: 550 (80 g/m²) Transparencies: 200 Labels: 200
Media type and capacity, tray 3	Sheets: 550 (80 g/m²) Transparencies: 200 Labels: 200
Media types	Paper (plain, heavy, extra heavy, glossy, light, recycle, tough), envelopes, labels, glossy film, cardstock, transparencies
Media weight (tray 1)	60 to 300 g/m² plain papers, up to 220 g/m² glossy/coated
Media weight (tray 2)	60 to 256 g/m² plain papers, up to 220 g/m² glossy/coated
Media weight (tray 3)	Optional 1x550 and 2x550 tray and stand: A3, A4, A4-R, A5, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 2700-sheet HCI paper tray and stand: A4
Media weight, supported	100-sheet multipurpose Tray 1: 60 to 300 g/m², 550-sheet input Tray 2: 60 to 256 g/m², 0ptional 1x550 and 2x550 tray and stand: 60 to 256 g/m², 0ptional 2700-sheet HCI paper tray and stand: 60 to 256 g/m²
Media weight, supported	100-sheet multipurpose Tray 1: 16 to 80 lb, 550-sheet input Tray 2: 16 to 68 lb, Optional 1x550 and 2x550 tray and stand: 16 to 68 lb, Optional 2700-sheet HCI paper tray and stand: 16 to 68 lb
Memory	1.5 GB
Memory Slots	1 slot, 144-pin DDR3 x32 SODIMM
Memory card compatibility	Not available
Memory upgrade	Expandable to 3.5 GB through 1 GB 144-pin DDR3 x32 SODIMM
Minimum System Requirements	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com;
Minimum System Requirements for Macintosh	2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com;
Number of print cartridges	4 toner cartridges (1 each for black, cyan, magenta, yellow)
Number of users	5-20 Users
Operating humidity range	10 to 80% RH
Operating temperature range	50 to 90.5°F
Operating temperature range	10 to 32.5℃
Orderable supplies	HP LaserJet Toner Collection Unit 3WT90A, HP LaserJet Managed 110V Fuser Kit 3WT87MC, HP LaserJet Managed 220V Fuser Kit 3WT88MC, HP LaserJet Managed Image Transfer Belt 3WT89MC, HP LaserJet Managed ITB Cleaning Unit 7HA22MC, HP LaserJet Managed Transfer Roller Kit 7HA23MC
Output capacity	Up to 250 sheets

Package dimensions (W x D x H)	786 x 736 x 558 mm
Package dimensions (W x D x H)	30.95 x 28.98 x 21.98 in
Package weight	116.75 lb
Package weight	53.05 kg
Pallet dimensions	31.1 x 29.92 x 92.9 in
Pallet dimensions (W x D x H)	790 x 760 x 2359 mm
Pallet weight	489 lb
Pallet weight	222.27 kg
Paper handling input, optional	Add up to two: 1x550-sheet paper tray; Add up to one: 2x550-sheet paper tray and stand, 2,700 (1,600+1,100) sheet high capacity input paper tray and stand, or Cabinet stand
Paper handling input, standard	100-sheet multipurpose tray, 550-sheet input tray
Paper handling output, standard	250-sheet output bin
Paper trays, maximum	6
Paper trays, standard	2
Plug and play	HP Smart Install
Power	Input voltage: 100 V to 127 V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 6 A. Not dual voltage, power supply varies by part
	number with # Option code identifier.
Print Technology	Laser
Print Technology Print colors	
	Laser
Print colors	Laser Yes HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP
Print colors  Print languages	Laser  Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™
Print colors  Print languages  Print quality black (normal)	Laser  Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)	Laser  Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)	Laser  Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 1200 x 1200 dpi
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)	Ves  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 600 x 600 dpi  Up to 600 x 600 dpi
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)  Print speed black (Landscape, A5)	Ves  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 600 x 600 dpi  Up to 600 x 600 dpi  Up to 35 ppm
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)  Print speed black (Landscape, A5)  Print speed black (normal, A3)	Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple Air Print™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 1200 x 600 dpi  Up to 600 x 600 dpi  Up to 35 ppm  Up to 26 ppm
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)  Print speed black (Landscape, A5)  Print speed black (normal, A3)  Print speed black (normal, tabloid)	Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 1200 x 600 dpi  Up to 600 x 600 dpi  Up to 35 ppm  Up to 26 ppm  Up to 26 ppm
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)  Print speed black (Landscape, A5)  Print speed black (normal, A3)  Print speed black (normal, tabloid)  Print speed color (Landscape, A5)	Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 1200 x 600 dpi  Up to 600 x 600 dpi  Up to 35 ppm  Up to 26 ppm  Up to 35 ppm  Up to 35 ppm
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)  Print speed black (Landscape, A5)  Print speed black (normal, A3)  Print speed black (normal, tabloid)  Print speed color (Landscape, A5)  Print speed color (normal, A3)	Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 1200 x 600 dpi  Up to 35 ppm  Up to 26 ppm  Up to 35 ppm  Up to 26 ppm  Up to 26 ppm
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)  Print speed black (Landscape, A5)  Print speed black (normal, A3)  Print speed black (normal, tabloid)  Print speed color (Landscape, A5)  Print speed color (normal, A3)  Print speed color (normal, tabloid)	Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 1200 x 200 dpi  Up to 600 x 600 dpi  Up to 35 ppm  Up to 26 ppm
Print colors  Print languages  Print quality black (normal)  Print resolution black (fine lines)  Print resolution color (fine lines)  Print resolution color (normal)  Print speed black (Landscape, A5)  Print speed black (normal, A3)  Print speed black (normal, tabloid)  Print speed color (Landscape, A5)  Print speed color (normal, A3)  Print speed color (normal, tabloid)  Print speed color (normal, tabloid)  Print speed duplex (A3)	Yes  HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™  Up to 600 x 600 dpi  Up to 1200 x 1200 dpi  Up to 1200 x 1200 dpi  Up to 600 x 600 dpi  Up to 35 ppm  Up to 26 ppm  Up to 35 ppm  Up to 26 ppm  Up to 26 ppm  Up to 26 ppm  Up to 26 ppm  Up to 18 ipm

Print speed duplex (tabloid) Print speed duplex (tabloid) Print speed duplex (tabloid) Print speed flotnote (AS)  [16] Print speed flotnote (AS) [16] Print technology  Laser  HP Printer Assistant; HP Device Toolbox HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource kit for HP Universal Print Driver (Oriver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)  Printer black pages (MPV black) Printer color pages (MPV color)  Processor speed  12 GHz  Product short name specifications  Quantity per pallet  4  RMN number  BOISB-1813-00  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended operating humidity range  Recommended operating temperature range  Recommended operating  15 to 27°C  Safety  Recommended operating (SP) to 80.6°F  Safety  Safety  Management Security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPP sec/Irrevall with Cartificate, Pre-Shared KQ authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in	Print speed duplex (letter)	Up to 45 ipm
Print speed duplex (tabloid)  Print speed footnote (AS)  Print technology  Laser  HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SIMP Proxy Agent; HP WS Pro Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource; ktf for HP Universal Print Driver Oriver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)  Printer black pages (MPV black)  Printer color pages (MPV black)  Processor speed  1.2 GHz  Product short name specifications  Roam; Two-sided printing  Quantity per pallet  4  RMN number  BOISB-1813-00  Recommended media weight (duplex)  Recommended media weight (duplex)  16 to 43 lb  Recommended media weight (duplex)  Recommended operating humidity and to 40,000(11)  Recommended operating temperature range  Recommended operating temperating temperature range  Recommended operating temperating temperating temperation tempera	Print speed duplex (letter)	Up to 45 ipm
Print speed footnote (AS)  Print technology  Laser  HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Oriver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)  Printer black pages (MPV black)  875  Printer color pages (MPV color)  Processor speed  1.2 GHz  Product short name specifications  Quantity per pallet  4  RMN number  BOISB-1813-00  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended operating humidity range  Recommended operating temperature range  Recommended operating temperature range  Recommended operating temperature range  Right margin (A4)  S mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014 (EG 60825-1:2014 (E	Print speed duplex (tabloid)	Up to 18 ipm
Printer Management  HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)  Printer black pages (MPV black)  875  Printer color pages (MPV color)  1625  Processor speed  1.2 GHz  Product short name specifications  Quantity per pallet  4  RMN number  BOISB-1813-00  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended operating humidity range  Recommended operating temperature range  Recommended operating temperature range  Recommended operating temperature range  Right margin (A4)  Som  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60925-1:2014/EC 60025-1:2014 (EG 60025-1:2014 (EG 60025-1:2014 (EG 60025-1:2014 (EG 60025-1:2014) (EG 60	Print speed duplex (tabloid)	Up to 18 ipm
Printer Management HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)  Printer black pages (MPV black) 875  Printer color pages (MPV color) 1625  Processor speed 1.2 GHz  Product short name specifications Roam; Two-sided printing  Quantity per pallet 4  RMN number 80ISB-1813-00  Recommended media weight (duplex) 60 to 163 g/m²  Recommended media weight (duplex) 16 to 43 lb  Recommended monthly page volume Up to 40,000[11]  Recommended operating humidity range 15 to 27°C  Recommended operating temperature range 15 to 27°C  Recommended operating temperature range 15 to 80.6°F  Right margin (A4) 5 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS certificate (Germany, Europe); Ul/CUL Listed and U Co CC (US/Canada); CAN/CSA C2.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040-10 and 1040-11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security; SNMP03, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-PLS), IPP over TLS, IPSec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Print speed footnote (A5)	[16]
Printer Management	Print technology	Laser
Printer color pages (MPV color)  Processor speed  1.2 GHz  Product short name specifications  HP Color Laser Jet Managed E75245dn, Print, Front-facing USB printing; Roam; Two-sided printing  Quantity per pallet  4  RMN number  B0ISB-1813-00  Recommended media weight (duplex)  60 to 163 g/m²  Recommended media weight (duplex)  16 to 43 lb  Recommended monthly page volume  Up to 40,000 <sup>[11]</sup> Recommended operating humidity range  Recommended operating temperature range  Fight margin (A4)  Smm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); 6S Certificate (Germany, Europe); UL/CUL Listed and UC coc (Us/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040-10 and 1040-11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 80.2.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPSec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Printer Management	JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed
Product short name specifications  HP Color Laser Jet Managed E75245dn, Print, Front-facing USB printing; Roam; Two-sided printing  Quantity per pallet  4  RMN number  B0ISB-1813-00  Recommended media weight (duplex)  60 to 163 g/m²  Recommended media weight (duplex)  Recommended monthly page volume  Up to 40,000 <sup>[11]</sup> Recommended operating humidity range  Recommended operating temperature range  Recommended operating temperature range  Recommended operating temperature range  Right margin (A4)  5 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/EC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/CUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040-10 and 1040-11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Printer black pages (MPV black)	875
Product short name specifications  HP Color Laser Jet Managed E75245dn, Print, Front-facing USB printing; Roam; Two-sided printing  Quantity per pallet  4  RMN number  BOISB-1813-00  Recommended media weight (duplex)  60 to 163 g/m²  Recommended media weight (duplex)  Recommended monthly page volume  Up to 40,000 <sup>[11]</sup> Recommended operating humidity range  Recommended operating temperature range  Recommended operating temperature range  From Sight margin (A4)  Som  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/EC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/CUL Listed and UC CoC (US/Canada); CAN/CSA C22-2, No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040-10 and 1040-11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Printer color pages (MPV color)	1625
Roam; Two-sided printing	Processor speed	1.2 GHz
Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended monthly page volume  Up to 40,000 <sup>[11]</sup> Recommended operating humidity range  Recommended operating temperature range  Right margin (A4)  5 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2011 +A2:2011 (Else EN 62479:2010/EC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Product short name specifications	
Recommended media weight (duplex)  Recommended media weight (duplex)  Recommended monthly page volume  Up to 40,000 <sup>[11]</sup> Recommended operating humidity range  Recommended operating temperature range  Recommended operating temperature range  15 to 27°C  Recommended operating temperature range  Fight margin (A4)  S mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UJ/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Quantity per pallet	4
Recommended media weight (duplex)  Recommended monthly page volume  Up to 40,000 <sup>[11]</sup> Recommended operating humidity range  Recommended operating temperature range  Right margin (A4)  S mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Security management  Security management  Anagement security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	RMN number	B0ISB-1813-00
Recommended monthly page volume  Recommended operating humidity range  Recommended operating temperature range  Recommended operating temperature range  Recommended operating temperature range  Recommended operating temperature range  Right margin (A4)  5 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Security management  Security management  Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	_	60 to 163 g/m²
Recommended operating humidity range  Recommended operating temperature range  Recommended operating temperature range  Recommended operating temperature range  Right margin (A4)  5 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Idass 1 Laser Product); EN 60825-1:2014/IEC 60825-1:2014 (Idass 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC COC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	<del></del>	16 to 43 lb
Recommended operating temperature range  Recommended operating temperature range  Right margin (A4)  5 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;		Up to 40,000 <sup>[11]</sup>
Recommended operating temperature range  Fight margin (A4)  Fight marg		30 to 70% RH
Right margin (A4)  5 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/CUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	, —	15 to 27°C
IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	•	59 to 80.6°F
+A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Right margin (A4)	5 mm
Security management authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication;	Safety	+A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by
	Security management	authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with

Standard input capacity (envelopes)	Up to 10
Standard media sizes (duplex)	A3; A4; A4-R; A5; 8K; 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm); B4 (JIS); B5 (JIS); Oficio; RA3; RA4; SRA3; SRA4
Standard media sizes (duplex, imperial)	Letter; Letter-R; Legal; Executive; Tabloid; Oficio (8.5 x 13 in)
Standard output capacity (envelopes)	Up to 50 envelopes
Standard output capacity (transparencies)	Up to 150 sheets
Storage device and direct print support	USB printing; Right-side facing USB/Flash drive
Storage temperature range	-4 to 104°F
Storage temperature range	-20 to 40°C
SureSupply supported	No
Target user and print volume	For teams up to 20 users; Prints up to 40,000 pages/month
Tariff numbers	8443321000 (EU Base HTS); 8443321010 (AM Base HTS); 84433231 (AP Base HTS)
Technology logo, print 1	Publication logos/AMS_EnergyStar.jpg
Technology logo, print 2	Publication logos/AMS_ windows_10.jpg
Technology logo, print 3	Publication logos/AMS_mac_hires.jpg
Technology logo, print 4	Publication logos/AMS_AirPrint.jpg
Technology logo, print 5	Publication logos/AMS_Mopria.jpg
Technology logo, print 6	Publication logos/AMS_hp_eprint.jpg
Top key features	Front-facing USB printing; Roam; Two-sided printing
Top margin (A4)	5 mm
Typical electricity consumption (TEC) footnote	BA TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115 V device.
Typical electricity consumption (TEC) number	2.11 kWh/Week (Blue Angel); 0.583 kWh/Week (Energy Star 3.0) <sup>[5]</sup>
UNSPSC code	43212105
UPC number	192018848269
Warm-up time	131 sec
Web address for additional information	Solutions: http://www.hp.com/go/gsc; Fonts and IPDS Emulation: http://www.hp.com/go/laserjetfonts; HP Web Jetadmin: http://www.hp.com/go/wja; HP Universal Print Driver: http://www.hp.com/go/upd; HP JetAdvantage Security Manager: http://www.hp.com/go/securitymanager; HP JetAdvantage On Demand Cloud Solutions: http://www.hp.com/go/JetAdvantageondemand

- [1] Standard cartridges included; yields 7,000 black and 6,000 color composite (C/M/Y) pages. Drums included; yields 75,000 black and color pages.
- [3] With print cartridges.
- [4] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device.
- [5] BA TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115 V device.
- [6] Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled.
- [7] Average black and color composite (C/M/Y) declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies
- [9] The Configuration Pages will report maximum memory at 2 GB after 1 GB DIMM installed. This is an expected behavior of this product.
- [10] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
- [11] HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.
- [12] Solution software available on 123.hp.com
- [13] EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.

# **HP Care Pack Services**

# Imaging and Printing Hardware Support Onsite Svc

HP 3 year Next Business Day w/DMR Service for Color LaserJet E75245 Managed	UB5A8E ★
HP 3 year 4 hour 9x5 w/DMR Service for Color LaserJet E75245 Managed	UB5B1E ★
HP 1 year Post Warranty 4 hour 9x5 w/DMR Service for Color LaserJet E75245 Managed	UB5B9PE
HP 1 year Post Warranty Next Business Day w/DMR Service for Color LaserJet E75245 Managed	UB5B7PE
HP 2 year Post Warranty 4 hour 9x5 w/DMR Service for Color LaserJet E75245 Managed	UB5C0PE
HP 2 year Post Warranty Next Business Day w/DMR Service for Color LaserJet E75245 Managed	UB5B8PE
HP 4 year 4 hour 9x5 w/DMR Service for Color LaserJet E75245 Managed	UB5B2E
HP 4 year Next Business Day w/DMR Service for Color LaserJet E75245 Managed	UB5A9E
HP 5 year 4 hour 9x5 w/DMR Service for Color LaserJet E75245 Managed	UB5B3E
HP 5 year Next Business Day w/DMR Service for Color LaserJet E75245 Managed	UB5B0E

★: Recommended

## **Imaging and Printing Commercial Care Pack Services**

HP Installation Service with network configuration for Workgroup Printer(1 unit)	U9JT2E ★
HP 1 year Post Wty Parts Exchange Service for Color LaserJet E75245 Managed	UB5C1PE
HP 2 year Post Wty Parts Exchange Service for Color LaserJet E75245 Managed	UB5C2PE
HP 3 year Parts Exchange Service for Color LaserJet E75245 Managed	UB5B4E
HP 4 year Parts Exchange Service for Color LaserJet E75245 Managed	UB5B5E
HP 5 year Parts Exchange Service for Color LaserJet E75245 Managed	UB5B6E
HP Fuser 110 Volt Maintenance Kit Repair Service for Color LaserJet M571	UC5H4E
HP Fuser 220 Volt Maintenance Kit Repair Service for Color LaserJet M571	UC5H5E
HP Intermediate Transfer Belt Maintenance Kit Repair Service for Color LaserJet M571	UC5H6E
HP Print Carbon Neutral Certification Service	U34Y1E
HP Toner Collection Unit Maintenance Kit Repair Service for Color LaserJet M571	UC5H7E

# Ink/Toner/Paper/Printer Supplies

# **HP Laser Toner Cartridges and Kits**

# **HP Laser Printer Supply Kits**

HP LaserJet 3WT90A Toner Collection Unit	3WT90A ★
HP LaserJet 3WT90A Toner Collection Unit	3WT90A ★
HP LaserJet 110V Fuser Kit	3WT87A
HP LaserJet 3WT88A 220V Fuser Kit	3WT88A
HP LaserJet 3WT89A Transfer Kit	3WT89A

★ : Recommended

# **HP Business Papers**

# **HP Business Papers for laser**

HP Enhanced Business Paper, Glossy, 150 g/m2, A4 (210 x 297 mm), 150 sheets	CG965A
HP Everyday Business Paper, Glossy, 32 lb, 11 x 17 in. (279 x 432 mm), 150 sheets	4WN07A
HP Everyday Business Paper, Glossy, 32 lb, 8.5 x 11 in. (216 x 279 mm), 150 sheets	4WN08A
HP Professional Business Paper, Glossy, 52 lb, 8.5 x 11 in. (216 x 279 mm), 150 sheets	4WN10A
HP Professional Business Paper, Matte, 52 lb, 8.5 x 11 in. (216 x 279 mm), 150 sheets	4WN05A

## Accessories

**Memory** ★: Recommended

## **DDR3 Memory**

HP 1 GB x32 144-pin (800 MHz)DDR3 SODIMM	E5K48A ★
HP 2 GB x32 144-pin (800 MHz) DDR3 SODIMM	E5K49A ★
HP 2GB 144-Pin DDR3 TAA Version DIMM	2NR09A ★

# **Paper Handling**

## **Input Trays**

HP Color LaserJet 2x550-sheet Feeder and Stand	T3V29A ★
HP LaserJet 2700-sheet High Capacity Paper Tray and Stand	T3V30A ★
HP LaserJet 550-sheet Paper Tray	T3V27A ★

## Fax Upgrades

HP MFP Analog Fax Accessory 700 2EH31A	HP MFP Analog Fax Accessory 700	2EH31A
--	---------------------------------	--------

# Cables/Cable Kits/Cable Adapters

#### **Printer Cables**

HP Foreign Interface Harness	B5L31A ★
Port Cables and Cable Adapters	

B5L28A ★

# **Security and Protection**

**HP Internal USB Ports** 

### **Smart Cards and SmartCard Readers**

HP HIP2 Keystroke Reader	Y7C05A ★
HP Legic Secure USB Reader	4QL32A ★
HP SmartCard NIPRNet Solution for US Government	CC543B ★
HP SmartCard SIPRNet Solution for US Government	F8B30A ★
HP USB Universal Card Reader	X3D03A ★

# **PC Drives and Storage**

### **EIO Hard Drives**

HP High-Performance Secure Hard Disk	B5L29A ★
HP TAA Version Secure Hard Disk Drive	5ELO3A ★
Network Print Servers	
External Print Servers	
HP Jetdirect 3100w BLE/NFC/Wireless Accessory	3JN69A ★
Internal Print Servers	
HP Jetdirect LAN Accessory	8FP31A ★
Cabinets and Stands	
Printer Cabinets and Stands	
HP LaserJet Printer Stand	T3V28A ★
Accessory Bundles	
Data Security Accessories	

2NR12A

HP Removable Hard Drive Enclosure

### **Solutions**

## **Imaging and Printing Solutions**

#### **Printing SW Solution Licenses**

HP HID Mobile Access Mifare DES Fire Keystroking Reader	35H11A ★
HP SIM for HID iClass for HIP2 Reader	Y7C07A ★

★: Recommended

### **HP Document and Workflow Solutions**

### **JetAdvantage Printing Security**

HP Access Control Secure Printing and Job Accounting Solution	HPACSOLUTION
HP Secure Print and Insights	HPJETADSECUREPRINT
HP Security Manager	HPJETADSECMGR
Pharos Blueprint	HP3PHAROSBPRNT

#### **JetAdvantage Print Management**

HP Universal Print Driver	HPUNIVPRNTDRV
HP Web Jetadmin	HPWEBJETADMIN
Kofax ControlSuite	HP_CSUITE
LRS VPSX for Output Management	HP3PLRS

# Disclaimer — Copyright

© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (us-en) – Nov 12, 2022 1:05 AM UTC+0000